
GLPI Installation

Release 9.5

GLPI Project, Teclib'

фев 08, 2022

1	Prerequisites	3
1.1	Web server	3
1.2	PHP	3
1.2.1	Mandatory extensions	3
1.2.2	Optional extensions	4
1.2.3	Configuration	4
1.3	Database	4
2	Install GLPI	7
2.1	Choose a version	7
2.2	Download	7
2.3	Installation	8
2.4	Files and directories locations	8
2.5	Post installation	9
3	Install wizard	11
3.1	Choose lang (Select your language)	11
3.2	License	11
3.3	Install / Update	12
3.3.1	Environment checks	13
3.3.2	Database connection	14
3.3.3	Database choice	14
3.3.4	Database initialization	15
3.3.5	Telemetry informations	16
3.3.6	End of installation	16
4	Timezones	19
4.1	Non windows users	19
4.2	Windows users	19
4.3	Grant access	20
5	Update	21
6	Command line tools	23
6.1	Console options	23
6.2	Additional install and update tools	24
6.2.1	Check requirements	24

6.2.2	Enable/Disable maintenance	24
6.3	Install	24
6.4	Database connection configuration	24
6.5	Update	25
6.6	Security key	25
6.7	Various tools	26
6.7.1	Database schema check	26
6.7.2	LDAP synchronization	26
6.7.3	Task unlock	27
6.8	Plugins tools	27
6.9	Migration tools	27
6.9.1	From MyISAM to InnoDB	27
6.9.2	Missing timestamps builder	28
6.9.3	Use timestamp data type	28
6.9.4	Migrate Domains plugin	28
6.9.5	Migrate Racks plugin	28
7	Advanced configuration	29
7.1	SSL connection to database	29

This documentation presents **GLPI** installation instructions.

GLPI (Gestion Libre de Parc Informatique) is a free (as in „free speech“ not as in „free beer“!) asset and helpdesk management solution accessible from a web browser built to manage all you asset management issues, from hardware components and software inventories management to user helpdesk management.

GLPI is a Web application that will need:

- a webserver;
- PHP;
- a database.

1.1 Web server

GLPI requires a web server that supports PHP, like:

- [Apache 2](#) (or more recent);
- [Nginx](#);
- [Microsoft IIS](#).

1.2 PHP

As of 9.5 release, GLPI requires [PHP 7.2](#) or more recent.

Note: We recommend to use the most recent stable PHP release for better performances.

1.2.1 Mandatory extensions

Following PHP extensions are required for the app to work properly:

- [curl](#): for CAS authentication, GLPI version check, Telemetry, ...;

- `fileinfo`: to get extra informations on files;
- `gd`: to generate images;
- `json`: to get support for JSON data format;
- `mbstring`: to manage multi bytes characters;
- `mysqli`: to connect and query the database;
- `session`: to get user sessions support;
- `zlib`: to get backup and restore database functions;
- `simplexml`;
- `xml`;
- `intl`.

1.2.2 Optional extensions

Note: Even if those extensions are not mandatory, we advise you to install them anyways.

Following PHP extensions are required for some extra features of GLPI:

- `cli`: to use PHP from command line (scripts, automatic actions, and so on);
- `domxml`: used for CAS authentication;
- `imap`: used for mail collector ou user authentication;
- `ldap`: use LDAP directory for authentication;
- `openssl`: secured communications;
- `xmlrpc`: used for XMLRPC API.
- `APCu`: may be used for cache; among others (see [caching configuration \(in french only\)](#)).

1.2.3 Configuration

PHP configuration file (`php.ini`) must be adapted to reflect following variables:

```
memory_limit = 64M ;           // max memory limit
file_uploads = on ;
max_execution_time = 600 ;     // not mandatory but recommended
session.auto_start = off ;
session.use_trans_sid = 0 ;    // not mandatory but recommended
```

1.3 Database

Warning: Currently, only [MySQL](#) (5.6 minimum) and [MariaDB](#) (10.0 minimum) database servers are supported by GLPI.

In order to work, GLPI requires a database server.



Proceed as follow:

1. Choose a version,
2. Download the archive,
3. Install :)

2.1 Choose a version

Note: It is highly recommended you choose the latest stable release for a production usage.

GLPI follows a semantic versioning scheme, on 3 digits. The first one is the major release, the second the minor and the third the fix release.

Major releases may come with important incompatibilities as well as new features; minor versions may bring new features as well, but stay perfectly compatible inside a major version.

Fixes releases will only fix reported issues without adding anything new.

2.2 Download

Warning: On GitHub, there are always two archives named *Source code* which should not be used.

Go to the *download* section of the [GLPI website](#) (or get archive directly from [Github release](#)) and choose the `glpi-{version}.tgz` archive.

2.3 Installation

Note: Packages may be available from your Linux distribution (Red Hat, CentOS, Fedora, Ubuntu, ...) that you should use with your standard packages manager as usual.

GLPI installation itself is composed of three steps:

1. Uncompress the archive in your website;
2. Give your webserver write access to the `files` and `config` directories;
3. *launch installation wizard* (or use the *command line installation script*).

Once these three steps have been completed the application is ready to be used.

If you need to set advanced configuration, like SSL connection parameters, please refer to *advanced configuration*.

2.4 Files and directories locations

Like many other web applications, GLPI can be installed by just copying the whole directory to any web server. However, this may be less secure.

Warning: Every file accessible directly from a web server must be considered unsafe!

GLPI stores some data in the `files` directory, the database access configuration is stored in the `config` directory, etc. Even if GLPI provides some ways to prevent files from being accessed by the webserver directly, best practise is to store data outside of the web root. That way, sensitive files cannot be accessed directly from the web server.

There are a few configuration directives you may use to achieve that (directives that are used in provided downstream packages):

- `GLPI_CONFIG_DIR`: set path to the configuration directory;
- `GLPI_VAR_DIR` : set path to the `files` directory;
- `GLPI_LOG_DIR` : set path to logs files.

Note: There are many other configuration directives available, the ones we talked about are the main to take into account for a more secure installation.

Directories choice is entirely up to you; the following example will follow the [FHS](#) recommendations.

Our GLPI instance will be installed in `/var/www/glpi`, a specific virtual host in the web server configuration will reflect this path.

GLPI configuration will be stored in `/etc/glpi`, just copy the contents of the `config` directory to this place. GLPI requires read rights on this directory to work; and write rights during the installation process.

GLPI data will be stored in `/var/lib/glpi`, just copy the contents of the `files` directory to this place. GLPI requires read and write rights on this directory.

GLPI logs files will be stored in `/var/log/glpi`, there is nothing to copy here, just create the directory. GLPI requires read and write access on this directory.

Following this instructions, we'll create a `inc/downstream.php` file into GLPI directory with the following contents:

```
<?php
define('GLPI_CONFIG_DIR', '/etc/glpi/');

if (file_exists(GLPI_CONFIG_DIR . '/local_define.php')) {
    require_once GLPI_CONFIG_DIR . '/local_define.php';
}
```

Warning: GLPI packages will certainly provide a `inc/downstream.php` file. This one must not be edited!

GLPI looks for a `local_define.php` file in its own `config` directory. If you want to use one form new config directory, you have to load it.

Then, create a file in `/etc/glpi/local_define.php` with the following contents:

```
<?php
define('GLPI_VAR_DIR', '/var/lib/glpi');
define('GLPI_LOG_DIR', '/var/log/glpi');
```

Note: New in version 9.2.2.

For GLPI prior to 9.2.2, the `GLPI_VAR_DIR` constant did not exist and it was required to set all paths separately:

```
<?php
define('GLPI_VAR_DIR', '/var/lib/glpi');
define('GLPI_DOC_DIR', GLPI_VAR_DIR);
define('GLPI_CRON_DIR', GLPI_VAR_DIR . '/_cron');
define('GLPI_DUMP_DIR', GLPI_VAR_DIR . '/_dumps');
define('GLPI_GRAPH_DIR', GLPI_VAR_DIR . '/_graphs');
define('GLPI_LOCK_DIR', GLPI_VAR_DIR . '/_lock');
define('GLPI_PICTURE_DIR', GLPI_VAR_DIR . '/_pictures');
define('GLPI_PLUGIN_DOC_DIR', GLPI_VAR_DIR . '/_plugins');
define('GLPI_RSS_DIR', GLPI_VAR_DIR . '/_rss');
define('GLPI_SESSION_DIR', GLPI_VAR_DIR . '/_sessions');
define('GLPI_TMP_DIR', GLPI_VAR_DIR . '/_tmp');
define('GLPI_UPLOAD_DIR', GLPI_VAR_DIR . '/_uploads');
define('GLPI_CACHE_DIR', GLPI_VAR_DIR . '/_cache');

define('GLPI_LOG_DIR', '/var/log/glpi');
```

Of course, it is always possible to redefine any of those paths `if` needed.

2.5 Post installation

Once GLPI has been installed, you're almost done.

An extra step would be to secure (or remove) installation directory. As an example, you can consider adding the following to your Apache virtual host configuration (or in the `glpi/install/.htaccess` file):

```
<IfModule mod_authz_core.c>
    Require local
</IfModule>
<IfModule !mod_authz_core.c>
    order deny, allow
    deny from all
    allow from 127.0.0.1
    allow from ::1
</IfModule>
ErrorDocument 403 "<p><b>Restricted area.</b><br />Only local access allowed.<br />Check your
↪ configuration or contact your administrator.</p>"
```

With this example, the *install* directory access will be limited to localhost only and will display an error message otherwise. Of course, you may have to adapt this to your needs; refer to your web server's documentation.



To begin installation process, point your browser to the GLPI main address: https://\protect\T2A\textbraceleftadresse_glpi\protect\T2A\textbraceright/

When GLPI is not installed; a step-by-step installation process begins.

3.1 Choose lang (Select your language)

The first step will let you choose the installation language. Select your lang, and click validate.



3.2 License


Usage of GLPI is subject to GNU license approval. Once licensing terms read and accepted, just validate the form.



If you do not agree with licensing terms, it is not possible to continue installation process.

3.3 Install / Update

This screen allows to choose between a fresh GLPI installation or an update.



Click on install.

3.3.1 Environment checks

This step will check if prerequisites are met. If they're not, it is not possible to continue and an explicit error message will tell you about what is wrong and what to do before trying again.

GLPI SETUP

Step 0

Checking of the compatibility of your environment with the execution of GLPI

Test done	Results
Testing PHP Parser	✓
Sessions test	✓
Test if Session_use_trans_sid is used	✓
mysqli extension test	✓
ctype extension test	✓
fileinfo extension test	✓
json extension test	✓
mbstring extension test	✓
zlib extension test	✓
curl extension test	✓
gd extension test	✓
simplexml extension test	✓
xml extension test	✓
imap extension test	✓
APCu extension test	✓
xmlrpc extension test	✓
ldap extension test	❗ ldap extension is not present
Zend OPcache extension test	❗ Zend OPcache extension is not present
Allocated memory test	✓
Checking write permissions for setting files	✓
Checking write permissions for document files	✓
Checking write permissions for dump files	✓
Checking write permissions for session files	✓
Checking write permissions for automatic actions files	✓
Checking write permissions for graphic files	✓
Checking write permissions for lock files	✓
Checking write permissions for plugins document files	✓
Checking write permissions for temporary files	✓
Checking write permissions for cache files	✓
Checking write permissions for rss files	✓
Checking write permissions for upload files	✓
Checking write permissions for pictures files	✓
Checking write permissions for log files	✓
SELinux mode is Enforcing	✓
SELinux boolean configuration for httpd_can_network_connect --> on	✓
SELinux boolean configuration for httpd_can_network_connect_db --> on	✓
SELinux boolean configuration for httpd_can_sendmail --> on	✓


Do you want to continue?

[Continue](#) [Try again](#)

Some prerequisites are optionals, it will be possible to continue installation event if they're not met.

3.3.2 Database connection

Database connection parameters are asked.



The screenshot shows the GLPI Setup interface. At the top left is the GLPI logo. The title 'GLPI SETUP' is in yellow. Below it, 'Step 1' and 'Database connection setup' are in white. A white box contains the 'Database connection parameters' section with three input fields: 'SQL server (MariaDB or MySQL)', 'SQL user', and 'SQL password'. An orange 'Continue' button is at the bottom right of the form.

- *MySQL server*: enter the path to your MySQL server, *localhost* or *mysql.domaine.tld* as example;
- *MySQL user*: enter user name that is allowed to connect to the Database;
- *MySQL password*: enter user's password.

Once all fields are properly filled, validate the form.

A first database connection is then established. If parameters are invalid, an error message will be displayed, and you'll have to fix parameters and try again.

3.3.3 Database choice

Once connection to the database server is OK, you have to create or choose the database you want for your GLPI and init it.



There are 2 ways to go:

- use an existing database

Select this database in the displayed list. Validate to use.

Warning: Selected database contents will be destroyed on installation.

- Create a new database

Choose *Create a new database*, enter the database name in the relevant field and then validate to create the base.

Warning: SQL user must be able to create new database for this option to work.

3.3.4 Database initialization


This step initializes the database with default values.



If there is any error; pay attention to the displayed informations.


3.3.5 Telemetry informations

GLPI will ask you to share some Telemetry informations and to register. This is not mandatory.



3.3.6 End of installation

This step presents a summary of the installation and give created users list. Please pay attention to those informations and validate to go to the app.



Note: Default user accounts are:

- *glpi/glpi* admin account,
- *tech/tech* technical account,
- *normal/normal* „normal“ account,
- *post-only/postonly* post-only account.

Warning: For obvious security concerns, you'll have to delete or edit those accounts.

Before removing the *glpi* account, please make sure you have created another user with **super-admin** profile.



In order to get timezones working on a MariaDB/MySQL instance, you will have to initialize Timezones data and grant GLPI database user read ACL on their table.

Warning: Enabling timezone support on your MySQL instance may affect other database in the same instance; be carefull!

Warning: Currently, MySQL and MariaDB have a maximum date limited to 2038-01-19 on fields relying on `timestamp` type!

4.1 Non windows users

On most systems, you'll have to initialize timezones data from your system's timezones:

```
mysql_tzinfo_to_sql /usr/share/zoneinfo | mysql -p -u root mysql
```

You may want to check [MariaDB documentation about mysql_tzinfo_to_sql](#) and your system documentation do know where data are stored (if not in `/usr/share/zoneinfo`).

Do not forget to restart the database server once command is successfull.

4.2 Windows users

Windows does not provide timezones informations, you'll have to download and intialize data yourself.

See [MariaDB documentation about timezones](#).

4.3 Grant access

Warning: Be carefull not to give your GLPI database user too large access. System tables should **never** grant access to app users.

In order to list possible timezones, your GLPI database user must have read access on `mysql.time_zone_name` table. Assuming your user is `glpi@localhost`, you should run something like:

```
GRANT SELECT ON `mysql`.`time_zone_name` TO 'glpi'@'localhost';  
FLUSH PRIVILEGES;
```



Note: As for every update process, you have to backup some data before processing any upgrade:

- **backup your database;**
- backup your files directory;
- backup your configuration.

First, download latest GLPI version and extract files. GLPI update process is then automated. To start it, just go to your GLPI instance URI, or (recommended) use the *command line tools*.

Once a new version will be installed; you will not be able to use the application until a migration has been done.

Please also note the update process will automatically disable your plugins.

Warning: You should not try to restore a database backup on a non empty database (say, a database that has been partially migrated for any reason).

Make sure your database is empty before restoring your backup and try to update, and repeat on fail.



Command line tools

Since GLPI 9.2.2, command line tools are provided as supported scripts and are available from the `scripts` directory of the archive. On previous versions, those scripts were present in the `tools` directory that is not official and therefore not in the release archive.

Since GLPI 9.4.0, command line tools are being centralized in a console application (`bin/console`). Calling `php bin/console` from GLPI directory displays the list of available commands.

Note: If APCu is installed on your system, it may fail from command line since default configuration disables it from command-line. To change that, set `apc.enable_cli` to `on` in your APCu configuration file.

Warning: When using cli tools, please check the system user you are currently logged in with, and permissions on files and directories. With a wrong user, logs, cache and other files may be created with rights that would not allow your webserver to read or write on those files!

6.1 Console options

For every console command, following options are available:

- `--config-dir=CONFIG-DIR` path of configuration directory to use, relative to current working directory (required only if a custom path is used)
- `-h`, `--help` displays command help
- `--lang=LANG` output language code (default value is existing GLPI „language“ configuration or „en_GB“)
- `-n`, `--no-interaction` disable command interactive questions
- `--no-plugins` disable GLPI plugins during command execution
- `-q`, `--quiet` disable command output

- `-v|vv|vvv, --verbose=VERBOSE` verbosity level: 1 for normal output, 2 for more verbose output and 3 for debug

6.2 Additional install and update tools

6.2.1 Check requirements

Before installing or upgrading, requirements are automatically checked; but you can run them separately and see state for all of them using the `glpi:system:check_requirements` command.

6.2.2 Enable/Disable maintenance

GLPI provides a maintenance mode that can be activated prior to an update, and deactivated after all has been checked.

Just use the `glpi:maintenance:enable` and `glpi:maintenance:disable` commands.

6.3 Install

The `php bin/console db:install` has been made to install GLPI database in CLI mode.

Possible options for this command are:

- `-r, --reconfigure` to enable overriding of any existing DB configuration file
- `-f, --force` to force execution of installation even if database is not empty
- `-L, --default-language=DEFAULT_LANGUAGE` default language of GLPI (*en_GB* per default)
- `-H, --db-host=DB_HOST` host name (*localhost* per default)
- `-P, --db-port=DB_PORT` database port (default MySQL port if option is not defined)
- `-d, --db-name=DB_NAME` database name
- `-u, --db-user=DB_USER` database user name
- `-p, --db-password=DB_PASSWORD` database user's password (use it without value to be prompted for password)

If mandatory options are not specified in the command call, the console will ask for them.

Database connection parameters may be omitted if a configuration file already exists.

See also *console options*.

6.4 Database connection configuration

New in version 9.5.0.

The `php bin/console db:configure` has been made to define database connection parameters in CLI mode.

Possible options for this command are:

- `-r, --reconfigure` to enable overriding of any existing DB configuration file

- `-H, --db-host=DB_HOST` host name (*localhost* per default)
- `-P, --db-port=DB_PORT` database port (default MySQL port if option is not defined)
- `-d, --db-name=DB_NAME` database name
- `-u, --db-user=DB_USER` database user name
- `-p, --db-password=DB_PASSWORD` database user's password (use it without value to be prompted for password)

If mandatory options are not specified in the command call, the console will ask for them.

See also *console options*.

6.5 Update

The `php bin/console db:update` has been made to update GLPI database in CLI mode from a previously installed version.

There is no required arguments, just run the command so it updates your database automatically.

Warning: Do not forget to backup your database before any update try!

Possible options for this command are:

- `-u, --allow-unstable` allow update to an unstable version (use it with cautions)
- `-f, --force` force execution of update from v-1 version of GLPI even if schema did not changed

See also *console options*.

6.6 Security key

New in version 9.4.6.

Note: GLPI key file is available for GLPI \geq 9.4.6 but is not mandatory. As of GLPI 9.5, using the key file will be mandatory.

In order to store some sensitive data, GLPI relies on a homemade encryption/decryption tool, which uses a key to:

- encrypt data before storing them in the database,
- decrypt data that has been retrieved from the database.

The `php bin/console glpi:security:change_key` command allows to change the key, if it has been compromised for example. By default, command will:

- generate a new key and store it in the key file,
- update all configured fields (for core and compatible plugins) to use the new key,
- update all configuration entries listed (for core and compatible plugins) to use the new key.

6.7 Various tools

6.7.1 Database schema check

The `php bin/console db:check` command can be used to check if your database schema differs from expected one.

If you have any diff, output will look like :

```
$ php bin/console glpi:database:check
Table schema differs for table "glpi_rulecriterias".
--- Original
+++ New
@@ @@
 create table `glpi_rulecriterias` (
   `id` int(11) not null auto_increment
   `rules_id` int(11) not null default '0'
   `criteria` varchar(255) default null
   `condition` int(11) not null default '0'
-  `pattern` text default null
+  `pattern` text
   primary key (`id`)
```

6.7.2 LDAP synchronization

The `bin/console glpi:ldap:synchronize_users` command can be used to synchronize users against LDAP server informations.

Possible options for this command are:

- `-c, --only-create-new` only create new users
- `-u, --only-update-existing` only update existing users
- `-s, --ldap-server-id[=LDAP-SERVER-ID]` synchronize only users attached to this LDAP server (multiple values allowed)
- `-f, --ldap-filter[=LDAP-FILTER]` filter to apply on LDAP search
- `--begin-date[=BEGIN-DATE]` begin date to apply in „modifyTimestamp“ filter
- `--end-date[=END-DATE]` end date to apply in „modifyTimestamp“ filter
- `-d, --deleted-user-strategy[=DELETED-USER-STRATEGY]` force strategy used for deleted users:
 - 0: Preserve
 - 1: Put in trashbin
 - 2: Withdraw dynamic authorizations and groups
 - 3: Disable
 - 4: Disable + Withdraw dynamic authorizations and groups

See <http://php.net/manual/en/datetime.formats.php> for supported date formats in `--begin-date` and `--end-date` options.

See also *console options*.

6.7.3 Task unlock

The `php bin/console task:unlock` command can be used to unlock stucked cron tasks.

Warning: Keep in mind that no task should be stucked except in case of a bug or a system failure (database failure during cron execution for example).

Possible options for this command are:

- `-a, --all` unlock all tasks
- `-c, --cycle[=CYCLE]` execution time (in cycles) from which the task is considered as stuck (delay = task frequency * cycle)
- `-d, --delay[=DELAY]` execution time (in seconds) from which the task is considered as stuck (default: 1800)
- `-t, --task[=TASK]` itemtype::name of task to unlock (e.g: MailCollector::mailgate)

See also *console options*.

6.8 Plugins tools

New in version 9.5.

Some command line tools are also available to manage plugins from command line:

- `glpi:plugin:install`
- `glpi:plugin:activate`
- `glpi:plugin:deactivate`

In order to install MyGreatPlugin, you should end with something like:

```
$ ./bin/console glpi:plugin:install MyGreatPlugin
$ ./bin/console glpi:plugin:activate MyGreatPlugin
```

Each of those plugin commands can take a plugin name as argument, or the `--all` flag to be ran on all plugins.

6.9 Migration tools

6.9.1 From MyISAM to InnoDB

New in version 9.3.0.

Since version 9.3.0, GLPI uses the InnoDB engine instead of previously used MyISAM engine.

The `php bin/console glpi:migration:myisam_to_innodb` command can be used to migrate exiting tables to InnoDB engine.

6.9.2 Missing timestamps builder

New in version 9.1.0.

Prior to GLPI 9.1.0, fields corresponding to creation and modification dates were not existing.

The `php bin/console glpi:migration:build_missing_timestamps` command can be used to rebuild missing values using available logs.

6.9.3 Use timestamp data type

New in version 9.5.0.

Many date fields were using the `DATETIME` type, but this does not allow to rely on timezones. Timezone support requires all fields to use `TIMESTAMP` data type, but this query can be very long and therefore is not included in the standard update process.

Using the `glpi:migration:timestamps` command will change those fields to the correct data type, but read *documentation on timezones* before.

Warning: Ensure to backup your database before!

6.9.4 Migrate Domains plugin

New in version 9.5.0.

Domains in GLPI have evolved from a simple dropdown to a more complex object, including records management among others. Therefore, the Domains plugins feature are now included in core.

To migrate your plugin data; use the `glpi:migration:domains_plugin_to_core` command. Presence of the plugin is mandatory so checks can be run, you can use the `--without-plugin` switch but this is not recommended. If you were using an older version of the plugin than the one required, you can use the `--update-plugin` flag.

At the end, all domains types, domains and item relations will be migrated in core tables.

6.9.5 Migrate Racks plugin

New in version 9.5.0.

Since GLPI 9.3.0, data center infrastructure management is available as a core feature. A migration script from Racks plugin was provided inside the `scripts` directory. Since GLPI 9.5.0, this migration script has been refactored and moved inside the CLI console.

To migrate your plugin data; use the `glpi:migration:racks_plugin_to_core` command. Presence of the plugin is mandatory so checks can be run, you can use the `--without-plugin` switch but this is not recommended. If you were using an older version of the plugin than the one required, you can use the `--update-plugin` flag.



7.1 SSL connection to database

New in version 9.5.0.

Once installation is done, you can update the `config/config_db.php` to define SSL connection parameters. Available parameters corresponds to parameters used by `mysqli::ssl_set()`:

- `$dbssl` defines if connection should use SSL (*false* per default)
- `$dbsslkey` path name to the key file (*null* per default)
- `$dbsslcert` path name to the certificate file (*null* per default)
- `$dbsslca` path name to the certificate authority file (*null* per default)
- `$dbsslcapath` pathname to a directory that contains trusted SSL CA certificates in PEM format (*null* per default)
- `$dbsslcacipher` list of allowable ciphers to use for SSL encryption (*null* per default)

Warning: For now it is not possible to define SSL connection parameters prior or during the installation process. It has to be done once installation has been done.

